



W1

Multi Crimp Ring

Multi crimp rings are designed especially for use in the automotive sector.

They are particularly useful when used as a mandrel in the case of applications using soft hoses. The crimp ring can be fitted inside the hose and used to ensure a leak-proof joint when combined with a standard hose clamp mounted on the outer wall of the hose.

* Special material, finishes and diameters available on request.

Multi Crimp Ring W1

Application Ø		Part nº W1	Internal Ø	Thickness	Colour	Box Quantity (MOQ)	Packing
mm	inches						
20	25/32	03036084	20	1,2	SILVER-WHITE	50	400
22	55/64	03036126	22	1,2	SILVER-WHITE	50	400
24	15/16	03036168	24	1,2	SILVER-WHITE	50	400
26	1-1/32	03036200	26	1,2	SILVER-WHITE	50	400
27	1-1/16	03036221	27	1,2	SILVER-WHITE	50	400
28	1-7/64	03036242	28	1,2	SILVER-WHITE	50	400
29	1-9/64	03036263	29	1,2	SILVER-WHITE	50	400
30	1-3/16	03036284	30	1,2	SILVER-WHITE	50	400
31	1-7/32	03036305	31	1,2	SILVER-WHITE	50	400
32	1-17/64	03036326	32	1,2	SILVER-WHITE	50	400
33	1-19/64	03036347	33	1,2	SILVER-WHITE	50	400
34	1-11/32	03036368	34	1,2	SILVER-WHITE	50	400
35	1-3/8	03036389	35	1,2	SILVER-WHITE	50	400
36	1-27/64	03036400	36	1,2	SILVER-WHITE	50	400
37	1-29/64	03036421	37	1,2	SILVER-WHITE	50	400
38	1-1/2	03036442	38	1,2	SILVER-WHITE	50	400
39	1-17/32	03036463	39	1,2	SILVER-WHITE	50	400
40	1-37/64	03036484	40	1,2	SILVER-WHITE	50	400
41	1-39/64	03036505	41	1,2	SILVER-WHITE	50	400
42	1-21/32	03036526	42	1,2	SILVER-WHITE	50	400
43	1-11/16	03036547	43	1,2	SILVER-WHITE	50	400
44	1-47/64	03036568	44	1,2	SILVER-WHITE	50	400
45	1-49/64	03036589	45	1,2	SILVER-WHITE	50	400
46	1-13/16	03036600	46	1,2	SILVER-WHITE	50	400
47	1-27/32	03036621	47	1,2	SILVER-WHITE	50	400
48	1-57/64	03036642	48	1,2	SILVER-WHITE	50	400
49	1-59/64	03036663	49	1,2	SILVER-WHITE	50	400
50	1-31/32	03036684	50	1,2	SILVER-WHITE	50	400

W1 Ring: St 34 steel (DIN 2393 C) **Finish:** Silver-white Cr3 Zinc-Plated