



## ADD Double-toothed lock washer

### Information

This washer is used in panel assembly using holes and grooves which are much bigger than the diameter of the screw or bolt, in order to achieve evenly distributed pressure over the entire area of contact. The ADD washer is also very useful when fastening two panels together. Lateral movement can be avoided as the panels remain fixed in a static position.

The diameter of the washer chosen should be far greater than the diameter of the hole or groove in order to ensure sufficient contact area. The advantage of the use of the ADD washer is that the specific pressure is spread over a greater surface area in materials which are softer than steel.

### ADD Double-toothed lock washer

Diameter $d_1$	Part n° ADD	s	$d_2 \pm 0,3$	Box quantity	Outer box quantity
4,5 $\pm 0,3$	01060012	0,5	14,0	1000	16000
5,5 $\pm 0,3$	01060020	0,5	17,0	1000	16000
6,5 $\pm 0,3$	01060039	0,6	20,5	1000	8000
8,5 $\pm 0,3$	01060055	0,8	23,0	1000	8000
10,5 $\pm 0,3$	01060063	1	26,0	1000	8000
13 $\pm 0,3$	01060071	1,1	31,0	500	4000

#### Material specifications:

SPRING STEEL  
HrC 43+49 (HV 425-495)

#### Surface treatment:

Anti-rust oil-dipped

