



## Multi Crimp Ring

Multi crimp rings are designed especially for use in the automotive sector.

They are particularly useful when used as a mandrel in the case of applications using soft hoses. The crimp ring can be fitted inside the hose and used to ensure a leak-proof joint when combined with a standard hose clamp mounted on the outer wall of the hose.

\* Special material, finishes and diameters available on request.

**W3**

### Multi Crimp Ring W3

Application Ø		Part n° W3	Internal Ø	Thickness	Colour	Box Quantity (MOQ)	Packing
mm	inches						
16	5/8	033036001	16	1,2	STAINLESS STEEL	50	400
17	43/64	033036022	17	1,2	STAINLESS STEEL	50	400
18	45/64	033036043	18	1,2	STAINLESS STEEL	50	400
19	3/4	033036064	19	1,2	STAINLESS STEEL	50	400
20	25/32	033036085	20	1,2	STAINLESS STEEL	50	400
21	55/64	033036106	21	1,2	STAINLESS STEEL	50	400
22	15/16	033036127	22	1,2	STAINLESS STEEL	50	400
23	1-1/32	033036148	23	1,2	STAINLESS STEEL	50	400
24	1-1/16	033036169	24	1,2	STAINLESS STEEL	50	400
25	1-7/64	033036180	25	1,2	STAINLESS STEEL	50	400
26	1-9/64	033036201	26	1,2	STAINLESS STEEL	50	400
27	1-3/16	033036222	27	1,2	STAINLESS STEEL	50	400
28	1-7/32	033036243	28	1,2	STAINLESS STEEL	50	400
29	1-17/64	033036264	29	1,2	STAINLESS STEEL	50	400
30	1-19/64	033036285	30	1,2	STAINLESS STEEL	50	400
31	1-11/32	033036306	31	1,2	STAINLESS STEEL	50	400
32	1-3/8	033036327	32	1,2	STAINLESS STEEL	50	400
33	1-27/64	033036348	33	1,2	STAINLESS STEEL	50	400
34	1-29/64	033036369	34	1,2	STAINLESS STEEL	50	400
35	1-1/2	033036380	35	1,2	STAINLESS STEEL	50	400
36	1-17/32	033036401	36	1,2	STAINLESS STEEL	50	400
37	1-37/64	033036422	37	1,2	STAINLESS STEEL	50	400
38	1-1/2	033036443	38	1,2	STAINLESS STEEL	50	400
39	1-17/32	033036464	39	1,2	STAINLESS STEEL	50	400
40	1-37/64	033036485	40	1,2	STAINLESS STEEL	50	400

**W3 Ring:** Stainless Steel (AISI 430) **Finish:** 100% Stainless steel