

ASFA High Torque Constant Tension Hose Clamp W3 Stainless Steel



The MIKALOR High Torque Constant Tension clamp has been designed to guarantee constant performance and torque values.

The screw is fitted with special conical washers, which adapt their behaviour according to the vibrations and temperature changes occurring in the application. Thanks to the 8 mm hexagonal screw and a bandwidth of 16 mm, we can increase the tightening torque by more than 118 % compared to the range with a bandwidth of 12 mm, while at the same time increasing the performance by 48 %.

Designed and manufactured with perfectly rounded band edges and a housing with a double fastening reinforcement.

Due to its high performance, it is especially used in industrial applications and in the agricultural machinery, naval and industrial vehicle sectors.

ØD Application +2	Part Number	L Max.	S +0.1	H Max.	a ±0.2	B Max.	T	Max. Pressure (BAR)	Max. Torque (Nm)	Box Qty.	Outer Box Qty.
25-45	03068001	73	0,85	14	16	22	8	55	14	50	50
32-54	03068002	73	0,85	14	16	22	8	50	14	50	50
45-67	03068003	73	0,85	14	16	22	8	45	14	50	50
57-79	03068004	73	0,85	14	16	22	8	40	14	50	50
70-92	03068005	73	0,85	14	16	22	8	30	14	50	50
83-105	03068006	73	0,85	14	16	22	8	20	14	25	25
95-118	03068007	73	0,85	14	16	22	8	17	14	25	25
108-130	03068008	73	0,85	14	16	22	8	14	14	25	25
121-143	03068009	73	0,85	14	16	22	8	11	14	25	25
133-156	03068010	73	0,85	14	16	22	8	8	14	25	25
146-168	03068011	73	0,85	14	16	22	8	6	14	25	25
159-181	03068012	73	0,85	14	16	22	8	5	14	25	25
172-194	03068013	73	0,85	14	16	22	8	4	14	25	25
184-206	03068014	73	0,85	14	16	22	8	3	14	25	25
197-219	03068015	73	0,85	14	16	22	8	2	14	25	25
210-232	03068016	73	0,85	14	16	22	8	2	14	25	25

* It is recommended to apply 75% of the maximum values contained in the table.

TECHNICAL INFORMATION	
MATERIAL	BAND AND HEAD: STAINLESS STEEL X6CR17 (DIN 1.4016) AISI-430 SCREW: STAINLESS STEEL. AISI-304 WASHERS: STAINLESS STEEL. AISI-304
FINISH	STAINLESS STEEL
CORROSION RESISTANCE	200 HOURS SALT SPRAY (ASTMB-117)
MAXIMUM TIGHTENING SPEED (RPM)	540 ±5

