

ASFA L (9 mm) Hose Clamp

Galvanized Steel - W1

Thanks to the exclusive design of the housing and the high- strength screw, the ASFA L Worm-Drive Clip has excellent performance while being at the same time very compact.

The cold-formed stamped 9 mm band, smoothed on the underside, combined with the bevelled band edges protects the hose from any damage.


DIN 3017. The ASFA LW1 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

*** The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.**

Ø	Part Number	A +0.3 -	L +1 -	S ±0.1	H Max.	B	Maximum Values		Box	Outer Box
							Pressure	Par		
8-12(*)	03008745	7	18,5	0,65	9,2	11,5	15	1,5	200	1.600
8-16	03008753	9	22,1	0,65	10,5	14,0	45	3,0	200	800
12-22	03008761	9	22,1	0,65	10,5	14,0	45	3,0	200	800
16-27	03008770	9	23,6	0,75	10,5	14,0	42	3,5	200	800
20-32	03008788	9	23,6	0,75	10,5	14,0	36	3,5	200	800
25-40	03008796	9	25,6	0,75	10,5	14,0	32	4,0	100	400
30-45	03008809	9	25,6	0,75	10,5	14,0	28	4,0	100	800
32-50	03008817	9	25,6	0,75	10,5	14,0	24	4,0	100	800
40-60	03008825	9	25,6	0,75	10,5	14,0	19	4,0	100	400
50-70	03008833	9	29,6	0,75	10,5	14,0	17	4,0	100	100
60-80	03008841	9	29,6	0,75	10,5	14,0	15	4,0	100	100
70-90	03008850	9	29,6	0,75	10,5	14,0	13	4,0	50	50
80-100	03008868	9	29,6	0,75	10,5	14,0	11	4,0	50	50
90-110	03008876	9	29,6	0,75	10,5	14,0	10	4,0	25	200
100-120	03008884	9	29,6	0,75	10,5	14,0	9	4,0	25	200
110-130	03008892	9	29,6	0,75	10,5	14,0	8	4,0	25	25
120-140	03008905	9	29,6	0,75	10,5	14,0	7	4,0	25	25
130-150	03008913	9	29,6	0,75	10,5	14,0	6	4,0	25	25
140-160	03008921	9	29,6	0,75	10,5	14,0	5	4,0	25	25

* It is recommended to apply 75% of the maximum values contained in the table.

(*) ASFA-M (7 mm) Hose Clamp.

	TECHNICAL INFORMATION	
	MATERIAL	STEEL BAND AND HOUSING W1 (DIN 1.0935) STEEL SCREW QST 36-3 (DIN 1.0214)
	FINISH	GALVANIZED
	CORROSION RESISTANCE	144 HOURS SALT SPRAY (ASTM B-117)
	MAXIMUM TIGHTENING SPEED (RPM)	540 ± 5

