

ASFA L 9mm Hose Clamp

AISI 430 Stainless Steel - W2



W2

Thanks to the exclusive design of the housing and the high- strength screw, the ASFA L Worm-Drive Clip has excellent performance while being at the same time very compact.

The cold-formed stamped 9 mm band, smoothed on the underside, combined with the bevelled band edges protects the hose from any damage.


DIN 3017. The ASFA LW1 hose clip complies fully with the DIN 3017 norm and also with the directive EU 2002/95/EC.

* The maximum application pressure can vary depending on the type of hose used and the geometry of the coupling.

							Maximum Values			
Ø Application	Part Number	A +0.3 - 0.2	L +1 - 0.5	S ±0.1	H Max.	B Max.	Pressure (Bar)	Par (Nm)	Box Quantity	Outer Box Quantity
8-12 (*)	03016508	7	18,5	0,4	9,2	11,5	15	1,5	200	1.600
8-16	03016516	9	22,1	0,6	10,5	14,0	45	3,0	200	800
12-22	03016524	9	22,1	0,6	10,5	14,0	45	3,0	200	800
16-27	03016532	9	23,6	0,7	10,5	14,0	42	3,5	200	800
20-32	03016540	9	23,6	0,7	10,5	14,0	36	3,5	200	800
25-40	03016559	9	25,6	0,7	10,5	14,0	32	4,0	100	400
30-45	03016567	9	25,6	0,7	10,5	14,0	28	4,0	100	800
32-50	03016575	9	25,6	0,7	10,5	14,0	24	4,0	100	800
40-60	03016583	9	25,6	0,7	10,5	14,0	19	4,0	100	400
50-70	03016591	9	29,6	0,7	10,5	14,0	17	4,0	100	100
60-80	03016604	9	29,6	0,7	10,5	14,0	15	4,0	100	100
70-90	03016612	9	29,6	0,7	10,5	14,0	13	4,0	50	50
80-100	03016620	9	29,6	0,7	10,5	14,0	11	4,0	50	50
90-110	03016639	9	29,6	0,7	10,5	14,0	10	4,0	25	200
100-120	03016647	9	29,6	0,7	10,5	14,0	9	4,0	25	200
110-130	03016655	9	29,6	0,7	10,5	14,0	8	4,0	25	25
120-140	03016663	9	29,6	0,7	10,5	14,0	7	4,0	25	25
130-150	03016671	9	29,6	0,7	10,5	14,0	6	4,0	25	25
140-160	03016680	9	29,6	0,7	10,5	14,0	5	4,0	25	25

* It is recommended to apply 75% of the maximum values contained in the table.

(*) ASFA-M (7 mm) Hose Clamp.

	TECHNICAL INFORMATION	
	MATERIAL	STAINLESS STEEL BAND AND HOUSING W2 AISI 430 X6Cr17 (DIN 1.4016) STEEL SCREW Qst 36-3 (DIN 1.0214)
	FINISH	STAINLESS STEEL
	CORROSION RESISTANCE	72 HOURS SALT SPRAY (ASTM B-117)
	MAXIMUM TIGHTENING SPEED (RPM)	540 ± 5

