

W1



## OEM Ear Clip


This clamp was designed for use in low and medium-pressure applications on assembly lines, due to its fast and easy locking system.

The design of the locking mechanism means that this clamp can be used in areas which are difficult to access. In this case, manual pliers can be used to mount the clip.

Another very important characteristic of this clamp is that, once it has been mounted, it is tamper-proof.

***\*This clamp is also available in AISI 304 and AISI 316 material upon request.***

| Ø A<br>Application ±0.3 | Part<br>Number | Ø B<br>Closed | C<br>±0.5 | D<br>±0.5 | E<br>±0.1 | F<br>+0.4 -0.1 | G<br>Max | Box<br>Quantity | Outer Box<br>Quantity |
|-------------------------|----------------|---------------|-----------|-----------|-----------|----------------|----------|-----------------|-----------------------|
| 10,0                    | 03030752       | 8,3           | 8         | 2,6       | 0,6       | 7              | 14,0     | 1.000           | 4.000                 |
| 13,3                    | 03030760       | 10,8          | 8         | 2,6       | 0,6       | 7              | 17,5     | 1.000           | 4.000                 |
| 15,7                    | 03030779       | 13,2          | 8         | 2,8       | 0,6       | 7              | 19,9     | 1.000           | 4.000                 |
| 17,5                    | 03030787       | 14,3          | 8         | 2,8       | 0,8       | 7              | 22,5     | 1.000           | 4.000                 |
| 17,8                    | 03030795       | 14,6          | 8         | 2,8       | 0,8       | 7              | 22,5     | 1.000           | 4.000                 |
| 18,5                    | 03030808       | 15,3          | 8         | 2,8       | 0,8       | 7              | 23,5     | 1.000           | 4.000                 |
| 20,5                    | 03030816       | 17,3          | 8         | 2,8       | 0,8       | 7              | 26,0     | 500             | 2.000                 |
| 29,5                    | 03030824       | 26,3          | 8         | 2,8       | 0,8       | 7              | 35,5     | 500             | 2.000                 |
| 31,6                    | 03030832       | 28,4          | 8         | 2,8       | 0,8       | 7              | 37,5     | 500             | 2.000                 |
| 39,6                    | 03030840       | 36,4          | 8         | 2,8       | 0,8       | 7              | 45,5     | 500             | 500                   |
| 40,5                    | 03030859       | 37,3          | 8         | 2,8       | 0,8       | 7              | 46,5     | 500             | 500                   |
| 45,5                    | 03030867       | 42,3          | 8         | 2,8       | 0,8       | 7              | 51,5     | 200             | 800                   |
| 47,0                    | 03030875       | 43,8          | 8         | 2,8       | 0,8       | 7              | 53,0     | 200             | 1.600                 |
| 51,5                    | 03030883       | 48,3          | 8         | 2,8       | 0,8       | 7              | 57,5     | 100             | 800                   |
| 52,5                    | 03030891       | 49,3          | 8         | 2,8       | 0,8       | 7              | 58,5     | 100             | 800                   |
| 65,5                    | 03030904       | 62,3          | 8         | 2,8       | 0,8       | 7              | 71,5     | 100             | 800                   |

|  | TECHNICAL INFORMATION   |                                    |
|-------------------------------------------------------------------------------------|-------------------------|------------------------------------|
|                                                                                     | MATERIAL                | STEEL DX51DÅZ 150<br>(EN 10215)    |
|                                                                                     | FINISH                  | SILVER GREY                        |
|                                                                                     | CORROSION<br>RESISTANCE | 144 HOURS SALT SPRAY<br>ASTM B-117 |

