



W1

## One ear clip

The use of one ear clips is an economical solution for many simple hose assemblies carrying air or fluids. They are ideal for use with simple hose assemblies which do not require high clamping force.

The practical design of ear clips means that they are easy, fast and safe to mount. They are also tamper-proof once mounted. The edges are rounded to avoid damage to the hose.

| Ø Application | Part Number | A ±0.2 | B ±0.2 | C ±0.2 | D +0.5 -0.2 | E +0.1 -0.02 | Max. Pressure (Bar) | Box Quantity | Outer Box Quantity |
|---------------|-------------|--------|--------|--------|-------------|--------------|---------------------|--------------|--------------------|
| 7-9           | 03012080    | 9,3    | 5,5    | 6,0    | 13,0        | 0,6          | 27                  | 1.000        | 8.000              |
| 8-10          | 03012072    | 10,3   | 6,0    | 6,0    | 14,0        | 0,8          | 27                  | 1.000        | 8.000              |
| 9-11          | 03012013    | 11,3   | 6,5    | 6,5    | 15,0        | 0,8          | 27                  | 1.000        | 8.000              |
| 10-12         | 03012021    | 12,3   | 7,0    | 6,5    | 16,0        | 0,8          | 27                  | 500          | 8.000              |
| 11-13         | 03012030    | 13,3   | 7,5    | 6,5    | 17,0        | 0,9          | 22                  | 500          | 8.000              |
| 12-14         | 03012048    | 14,3   | 8,0    | 7,0    | 18,5        | 1,0          | 22                  | 500          | 4.000              |
| 14-16         | 03012056    | 16,3   | 8,5    | 7,0    | 20,5        | 1,1          | 18                  | 500          | 4.000              |
| 16-18         | 03012064    | 18,3   | 9,0    | 7,0    | 23,0        | 1,1          | 18                  | 500          | 4.000              |

|  | TECHNICAL INFORMATION |                                  |
|--|-----------------------|----------------------------------|
|  | MATERIAL              | STEEL W1 DC04 (EN 10139)         |
|  | FINISH                | ZINC-PLATED Cr3                  |
|  | CORROSION RESISTANCE  | 72 HOURS SALT SPRAY (ASTM B-117) |

